

## SPECIFICATION OF NOZZLE FILLING COMPOUND

### NOZZLE FILLING COMPOUND

PRODUCT	GRAIN SIZE (MM)	INSTALLATION METHOD	SERVICE TEMPERATURE DEG.C.	MOISTURE %	FREE FLOW %	SiO2 %
<b>MAC NFC (SILICA)</b>	<b>0-2</b>	<b>FILLING</b>	<b>1750</b>	<b>NIL</b>	<b>97</b>	<b>97</b>
PRODUCT	GRAIN SIZE (MM)	INSTALLATION METHOD	SERVICE TEMPERATURE DEG.C.	MOISTURE %	FREE FLOW %	Cr2O3 %
<b>MAC NFC (CHROME)</b>	<b>0-2</b>	<b>FILLING</b>	<b>1750</b>	<b>NIL</b>	<b>97</b>	<b>20</b>
PRODUCT	GRAIN SIZE (MM)	INSTALLATION METHOD	SERVICE TEMPERATURE DEG.C.	MOISTURE %	FREE FLOW %	ZrO2 %
<b>MAC NFC (ZIRCON)</b>	<b>0-0.50</b>	<b>FILLING</b>	<b>1750</b>	<b>NIL</b>	<b>97</b>	<b>60</b>